

## 4' Wheeled Unit for Site Flexibility

Four removable caster wheels allow the Highlander Portable VPL to move to different entries—especially convenient for facilities such as schools or churches.

### Features & Benefits

- Non-skid platform with folding ramp
- Solid 42" high guard panels
- Constant-pressure paddle switch; emergency stop button
- Safety sensors stop lift at obstructions
- Electromechanical interlocking gate releases only at upper landing
- Optional frame or surface-mounted controls
- Optional key switch
- Code-compliant ASME A18.1; ETL listed
- Rated load: 750 lbs.

### Engineering Support

For more information, see [www.harmar.com](http://www.harmar.com) for specifications, visit [www.arcata.com](http://www.arcata.com), or call for a free copy of Harmar's *Highlander VPL Planning Guide*



Oyster white (standard) or custom RAL color options ensure an attractive blend with building aesthetics.

Specifications	CPL400P
Lifting Height:	CPL400P 53"
Rated Load:	750 lbs.
Convenience:	4 Caster Wheels, Automatic folding ramp
Power:	120 VAC 15A grounded circuit 240 VAC Optional
Control Circuit:	24 VAC (Low Voltage Controls)
Standard Platform:	36" x 54" platform with 42" high guard panels
Safety Features:	Constant pressure paddle switch with E-stop; Platform gate on exit side
Warranty:	2-year parts

